

DESCRIPTIONS

150W, AC/DC Enclosed Switching Power Supply



UL[®] US CE Report UK Report

UL62368-1 EN62368-1 BS EN62368-1

FEATURES

- Universal 85 - 264VAC or 120 - 370VDC Input voltage
- Accepts AC or DC input (dual-use of same terminal)
- Operating ambient temperature range: -30°C to +70°C
- Low standby power consumption, high efficiency
- High I/O isolation test voltage up to 4000VAC
- Low ripple & noise
- 150% peak power lasts 5S
- Output short circuit, over-current, over-voltage, over-temperature protection
- OVC III (designed to meet EN61558)
- Operating up to 5000m altitude

APPLICATIONS

- Industrial
- LED
- Street light control
- Electricity
- Security
- Telecommunications
- Smart home

Selection Guide

Certification	Part No*	Output Power (W)	Nominal Output Voltage and Current (Vo/Io)	Output Voltage Adjustable Range ADJ (V)	Efficiency at 230VAC (%) Typ.	Max. Capacitive Load (μF)
UL/EN/BS EN	AE150-2B-12	150	12V/12.5A	10.2-13.8	86	10000
EN/BS EN	AE150-2B-15	150	15V/10A	13.5 -18	87	6000
UL/EN/BS EN	AE150-2B-24	156	24V/6.5A	21.6 - 28.8	88	2400
EN/BS EN	AE150-2B-36	154.8	36V/4.3A	32.4 - 39.6	88	1200
	AE150-2B-48	158.4	48V/3.3A	43.2 -52.8	89	600

Note: 1. *Use suffix "Q" for conformal coating.

2. If the terminal cover is required, please order "PAA-033" for self-installation.

3. The product picture is for reference only. For details, please refer to the actual product.

Specifications



Product Specifications	Item		Operating Conditions		Min.	Typ.	Max.	Unit	
Input Specifications	Input Voltage Range		AC input		85	--	264	VAC	
			DC input		120	--	370	VDC	
	Input Voltage Frequency				47	--	63	Hz	
	Input Current		115VAC		--	--	4	A	
			230VAC		--	--	2		
	Inrush Current		115VAC		--	30	--		
			230VAC		--	60	--		
	Leakage Current		240VAC		< 0.75mA				
Hot Plug				Unavailable					
Output Specifications	Output Voltage Accuracy		Full load range	Normal temperature,	--	±1	--	%	
				high temperature		±3			
			Low temperature						
	Line Regulation		Rated load		--	±0.5	--		
	Load Regulation		0% - 100% load		--	±0.5	--		
	Ripple & Noise*		20MHz bandwidth (peak-to-peak value)		12V/15V	--	--	150	mV
					24V/36V/48V	--	--	200	
	Temperature Coefficient				--	±0.03	--	%/°C	
	Minimum Load				0	--	--	%	
	Stand-by Power Consumption				--	--	0.5	W	
	Hold-up Time		115VAC		8	--	--	ms	
			230VAC		16	--	--		
	Short Circuit Protection		Recovery time <5s after the short circuit disappear.		Hiccup, continuous, self-recovery				
	Over-current Protection				≥110% Io, for more than 5 seconds, turn off the output, power restart after recovery				
	Over-voltage Protection		12V		≤18VDC		Hiccup, self-recover		
			15V		≤21.75VDC				
24V			≤33.6VDC						
36V			≤48.6VDC						
48V			≤60VDC						
Over-temperature Protection				Output voltage turn off, self-recovery					
General Specifications	Isolation	Input - ⊕	Electric strength test for 1min., leakage current <10mA		2000	--	--	VAC	
		Input - output			4000	--	--		
		Output - ⊕			1250	--	--		
	Insulation Resistance	Input - ⊕	Test voltage: 500VDC		100	--	--	MΩ	
		Input - output			100	--	--		
		Output - ⊕			100	--	--		
	Operating				-30	--	+70	°C	

	Temperature							%RH
	Storage Temperature				-40	--	+85	
	Storage Humidity	Non-condensing			10	--	95	
	Operating Humidity				20	--	90	
	Switching Frequency				--	65	--	kHz
	Power Derating	Operating temperature derating	85-100VAC	-30 to -25℃	5	--	--	% /℃
			12V	+45 to +70℃	2	--	--	
			15/24/36/48V	+50 to +70℃	2.5	--	--	
		Input voltage derating		85-100VAC	1.33	--	--	% /VAC
	Safety Class				CLASS I			
MTBF	MIL-HDBK-217F@25℃			>300,000 h				
Warranty	Ambient temperature: <45℃			3 years				
Mechanical Specifications	Case Material	Metal (AL1100, SGCC)						
	Dimensions	159.00 x 97.00 x 30.00mm						
	Weight	410g (Typ.)						
	Cooling Method	Free air convection						
Note: *The “Tip and barrel method” is used for ripple and noise test, output parallel 47uF electrolytic capacitor and 0.1uF ceramic capacitor.								



Electromagnetic Compatibility (EMC)

Electromagnetic Compatibility (EMC)	Emissions (EMI)	CE	CISPR32/EN55032 CLASS B			
		RE	CISPR32/EN55032 CLASS B			
		Harmonic current	IEC/EN61000-3-2 CLASS A (≤80% Load)			
	Immunity (EMS)	ESD	IEC/EN61000-4-2	Contact ±6KV/Air ±8KV	Perf. Criteria A	
		RS	IEC/EN61000-4-3	10V/m	Perf. Criteria A	
		EFT	IEC/EN61000-4-4	±4KV	Perf. Criteria A	
		Surge	IEC/EN61000-4-5	line to line ±2KV/line to ground ±4KV	Perf. Criteria A	
		CS	IEC/EN61000-4-6	10Vr.m.s	Perf. Criteria A	
	Voltage dips, short interruptions and voltage variations immunity	IEC/EN61000-4-11 100% dip 1 periods, 30% dip 25 periods, 100% interruptions 250 periods		Perf. Criteria B		


Characteristic Curve



Note: 1. With an AC input between 85-127VAC and a DC input between 120-180VDC, the output power must be derated as per temperature derating curves;
2. This product is suitable for applications using natural air cooling.



Dimensions and Recommended



Note:

1. Unless otherwise specified, parameters in this datasheet were measured under the conditions of $T_a=25^\circ\text{C}$, humidity $<75\%$ RH with nominal input voltage and rated output load;
2. The room temperature derating of $5^\circ\text{C}/1000\text{m}$ is needed for operating altitude greater than 2000m;
3. All index testing methods in this datasheet are based on our company corporate standards;
4. In order to improve the efficiency at high input voltage, there will be audible noise generated, but it does not affect product performance and reliability;
5. Products are related to laws and regulations: see "Features" and "EMC";
6. The out case needs to be connected to PE ($\oplus$) of system when the terminal equipment in operating;
7. The output voltage can be adjusted by the ADJ, clockwise to increase;
8. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units.
9. The power supply is considered a component which will be installed into a terminal equipment.